

# LOW TEMP NON-SLIP COATING

**HEAVY DUTY, RESISTS ACIDS, CHEMICALS & SOLVENTS, WITHSTANDS HEAVY TRAFFIC**  
**RAPID HARDENING MATERIAL**

## CAUTIONARY INFORMATION:

DO NOT USE THIS PRODUCT BEFORE READING THE MATERIAL SAFETY DATA SHEET. DO NOT TRANSFER TO UNMARKED CONTAINERS. FOR INDUSTRIAL, INSTITUTIONAL AND COMMERCIAL USE ONLY. KEEP OUT OF REACH OF CHILDREN.

**IMPORTANT:** READ AND FOLLOW ALL MIXING DIRECTIONS BEFORE USING THIS PRODUCT.

All surfaces to be treated should be free from oil, grease, etc. Deteriorated or weak concrete should be removed until sound concrete is exposed.

## DIRECTIONS:

**MIXING INSTRUCTIONS:** Pour a quantity of the liquid resin in a clean container. Gradually add the POLYESTER NON SLIP FINISH powder to the liquid stirring until thoroughly mixed. Do not add anything extra to mix. Do not mix more than can be used within potlife of the material. Potlife is approximately 45 minutes.

**APPLICATION:** Firmly place the POLYESTER NON SLIP FINISH mixture to the desired depth using screed or trowel. Material may then be finished with a brush or trowel to achieve desired non-slip finish.

**CLEANING:** Clean all tools and any equipment after use with lacquer thinner.

To Re-Order **TZ-20-00** Please call **1-800-474-7294**

Recommendations for the use of this product are based on reliable tests. No guarantee of the results are implied where conditions are beyond our control. Under no circumstance or conditions, either expressed or implied, will the manufacturer be liable for damages in excess of the purchase price of this product.

20-00



**INTERSTATE  
PRODUCTS, INC.**

*"Your Road to Quality Environmental Products"*

6561 Palmer Park Circle Suite A

Sarasota, FL 34238

<https://store.interstateproducts.com>

International: 1-941-377-8610

USA Toll Free: **1-800-474-7294**