

# 22 oz. PVC Specifications

+ Advantage MVP Oli Boom 22 is a proprietary PVC formula in a lightweight 22 oz weight specifically engineered for oil boom applications. Once fabricated, the booms are relied on to keep the oil from spreading farther into the fishing and shrimping communities, environmentally sensitive grass beds and other sensitive wildlife habitats.

	ENGLISH	METRIC	TESTING METHOD
<b>Weight</b>	22 oz./yd <sup>2</sup>	745 g/m <sup>2</sup>	
<b>Widths</b>	up to 61'	up to 155 cm	
<b>Construction</b>	18 x 16/1" by 1300 x 1500	7 x 6/cm" by 1430 x 1650	
<b>Grab Tansile</b>	459 x 418 lbs/1"	2042 x 1859 N/2.5 cm	FS 5100 / ASTM D5034
<b>Tongue Gear</b>	140 x 150 lbs./1"	623 x 667 N/2.5 cm	FS 5134 / ASTM 02261
<b>Adhesion</b>	22 lbs./2"	98 N/5cm	FS 5970 / ASTM 0751
<b>Finish</b>	Matte	Matte	
<b>Cold Crack</b>	-30 F	-34 C	FS 5874/ ASTM 02136
<b>Treatments</b>	Anti-Mildew, UV	Anti-Mildew, UV	
<b>Fire Retardant</b>	None	None	
<b>Put-Up</b>	75 yds	69 m	