EPOXY PATCH KIT SEALER

BEFORE YOU START, READ THE APPLICATION INSTRUCTIONS COMPLETELY. MAKE SURE SURFACE HAS BEEN

PROPERLY PREPARED....MAKE SURE TEMPERATURE OF FLOOR AND MATERI-ALS IS BETWEEN 60 AND 85 DEGREES F. THE FLOOR MUST BE DRY AND FREE OF ALL OILS, GREASE, WAX AND DIRT.... ACID ETCH ALL BONDING SURFACE.

RECOMMENDATIONS AND LIMITATIONS The EPOXY TYPE NON SKID PATCH AND REPAIR KIT has been designed for use on floor areas which are subjected to abrasive traffic, impact and corrosive chemical spillage, such as alkalis, blood, fats, oil, salts, sugars, and many other chemicals. DO NOT USE EPOXY REPAIR KIT to wood or asphaltic materials. This kit may be installed on any structurally sound and properly prepared concrete, metal or ceramic tile surface

- 1. Sweep clean all areas to be repaired.
- Use appropriate cleaner to remove grease and other contaminants. Let area dry well.
- 3. Mix A & B cans thoroughly until uniform mixture. IWhen using a partial kit use 2 part Resin to 1 part Hardener. Once the parts are mixed material should be applied before gel occurs. About 90 minutes at room temperature.
- Add all the aggregate to A&B and mix. For less viscous mix use less aggregate.
- Resurface: Apply with trowel, skim coat to 1/16 inch. To repair: Apply to crack and smooth.
- Curing time at 75 deg F. minimum 12 hours. 24 hours for traffic and 48 hours for chemical spillage.

To Reorder More AC-680 Please call 1-800-474-7294

(CONCRETE)

EPOXY CRACK &
REPAIR KIT
PERMANENT
PATCH - REPAIR AND
RESURFACE

CONTAINS: - RESIN - HARDENER -

NOTE: CURING TIME WILL RANGE WITH TEMPERATURE.

Cooler temperatures will slow down cure rate and warmer temperatures will accelerate cure rate. In cooler weather where ground is below 65 degrees, heat may be applied to patch area for faster cure.

CAUTION:

Avoid skin contact with Part A and B and their mixture. The use of protective hand creams or rubber gloves is recommended. Thoroughly wash hands with soap and water after use. and especially before eating or smoking. Prolonged or repeated exposure to the components may cause dermatitis or allergic reactions in some individuals.

KEEP OUT OF REACH OF CHILDREN

REORDER FROM:

132077



INTERSTATE PRODUCTS, INC.

"Your Road to Quality Environmental Products"

6561 Palmer Park Circle Sute A • Sarasota FL 34238 https://store.interstateproducts.com 1-800-474-7294 941-377-8610