

RAPID CONCRETE PATCH

POLYESTER PATCH FORMULA

POLYESTER MORTAR MIX

Permanent 100 % Solids Patching, Resurfacing and Bonding Compound

CAUTIONARY INFORMATION:

DO NOT USE THIS PRODUCT BEFORE READING THE MATERIAL SAFETY DATA SHEET. FOR INDUSTRIAL/PROFESSIONAL USE ONLY. DO NOT TRANSFER TO UNMARKED CONTAINERS. KEEP OUT OF REACH OF CHILDREN.

1. CAUTION! FLAMMABLE LIQUID: Keep away from heat, sparks and open flame. No smoking.

2. WARNING! HARMFUL IF INHALED OR SWALLOWED: May causes irritation of skin, eyes, nose and throat. Avoid breathing vapor. Use only with adequate ventilation. Keep container closed when not in use. Wash hands after handling. Wash clothing before re-use. Do not transfer contents to bottles or other unlabeled containers. **KEEP OUT OF REACH OF CHILDREN!**

3. FIRST AID: On contact, flush eyes or skin with plenty of water for at least 15 minutes. Remove contaminated shoes and clothing. If not breathing, give artificial respiration and/or administer oxygen. If swallowed, induce vomiting. **CALL A PHYSICIAN.**

Polyester Patch is a unique and complete pre-mixed polyester mortar. Usage is simple even under the most extreme conditions. When mixed, Polyester Patch provided high strength patching mortar, which can be feather-edged.

Polyester Patch may be used in areas with wide temperature ranges.

Polyester Patch will cure and set to a molecular bond in 25 minutes at 0° - 32° F.

Polyester Patch will cure and set in 15 minutes at temperatures exceeding 32° F.

Complete with aggregate nothing else to mix.

Easy to apply, gives professional results.

DIRECTIONS:

Clean surfaces of loose aggregate, dirt, grease, and oil. (For best results, heavy grease and imbedded oil should be removed with cleaner/degreaser). Allow to dry thoroughly. Remove gallon can of resin, pour all of powdered material onto clean cardboard, pour all of resin back in to shipping container and add powdered material slowly, mixing constantly. For best results use lo-speed electric drill.

THIS INFORMATION APPLIES TO THE SHORT POT LIFE OF MATERIAL, APPROXIMATELY 15 TO 20 MINUTES ONLY AFTER MIXING OR TO THE LIQUID ANY TIME THAT IT IS IN THE LIQUID STATE.

TO ORDER MORE **TZ-10-44** CALL 1-800-474-7294

Recommendations for the use of this product are based on reliable tests. No guarantee of results are implied where conditions are beyond our control. Under no circumstances or conditions, either expressed or implied, will the manufacturer be liable for damages in excess of the purchase price of this product.

10-44



INTERSTATE
PRODUCTS, INC.

"Your Road to Quality Environmental Products"

6561 Palmer Park Circle Sute A • Sarasota FL 34238

<https://store.interstateproducts.com>

1-800-474-7294 941-377-8610