# CPC

# SAFETY DATA SHEET

## 1. Identification

Product number 1000009631

Product identifier TERAND AUTO INTERIOR DETAILER & PROTECTOR

Company information CPC

1005 S. Westgate Drive

Addison, IL 60101 United States

Company phone General Assistance 630-543-7600

Emergency telephone US 1-866-836-8855 Emergency telephone outside 1-952-852-4646

US

Version # 01
Recommended use POLISH
Recommended restrictions None known.

# 2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1

Health hazardsNot classified.Environmental hazardsNot classified.OSHA defined hazardsNot classified.

Label elements



Signal word Danger

**Hazard statement** Extremely flammable aerosol.

**Precautionary statement** 

**Prevention** Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open

flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Response Wash hands after handling.

**Storage** Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal Not available.

Hazard(s) not otherwise None known.

classified (HNOC)

Supplemental information None.

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Butane		106-97-8	2.5 - 10
Propane		74-98-6	1 - 2.5
Other components below reportal		90 - 100	

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

## 4. First-aid measures

InhalationIf symptoms develop move victim to fresh air. Get medical attention if symptoms persist.Skin contactWash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Product name: TERAND AUTO INTERIOR DETAILER & PROTECTOR

Product #: 1000009631 Version #: 01 Issue date: 06-03-2015

Ingestion

Most important

symptoms/effects, acute and delayed

In the unlikely event of swallowing contact a physician or poison control center.

Direct contact with eyes may cause temporary irritation.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically.

**General information** 

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

## 5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters

Fire-fighting equipment/instructions

Contents under pressure. Pressurized container may explode when exposed to heat or flame.

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not

breathe fumes.

General fire hazards

Specific methods

Extremely flammable aerosol.

## 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

**Environmental precautions** 

Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

## Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value		
Propane (CAS 74-98-6)	PEL	1800 mg/m3		
		1000 ppm		
<b>US. ACGIH Threshold Limit Valu</b>	es			
Components	Туре	Value		
Butane (CAS 106-97-8)	STEL	1000 ppm		
US. NIOSH: Pocket Guide to Chemical Hazards				
Components	Туре	Value		
Butane (CAS 106-97-8)	TWA	1900 mg/m3		
		800 ppm		
Propane (CAS 74-98-6)	TWA	1800 mg/m3		

Biological limit values No biological exposure limits noted for the ingredient(s).

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

1000 ppm

Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Hand protection** Wear appropriate chemical resistant gloves.

Skin protection

Other Wear suitable protective clothing.

Respiratory protection If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an

air-supplied respirator.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

#### 9. Physical and chemical properties

**Appearance** 

Physical state
Form
Color
Not available.

Odor
Not available.

Odor threshold
Not available.

PH
Not available.

Melting point/freezing point
Not available.

Initial boiling point and boiling
Not available.

range

Flash point -156.0 °F (-104.4 °C) PROPELLANT estimated

Evaporation rate Not available.
Flammability (solid, gas) Not available.
Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available.

Product name: TERAND AUTO INTERIOR DETAILER & PROTECTOR

Product #: 1000009631 Version #: 01 Issue date: 06-03-2015

Explosive limit - upper (%) Not available.

Vapor pressure 50 - 70 psig @20C estimated

Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Specific gravity 0.901 estimated

## 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

**Conditions to avoid**Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materialsStrong oxidizing agents. Nitrates. Fluorine. Chlorine.Hazardous decompositionNo hazardous decomposition products are known.

products

## 11. Toxicological information

#### Information on likely routes of exposure

**Ingestion** Expected to be a low ingestion hazard.

Inhalation Not available.

Skin contactNo adverse effects due to skin contact are expected.Eye contactDirect contact with eyes may cause temporary irritation.Inproms related to theDirect contact with eyes may cause temporary irritation.

Symptoms related to the physical, chemical and toxicological characteristics

## Information on toxicological effects

#### **Acute toxicity**

Components	Species	Test Results
Butane (CAS 106-97-8)		
Acute		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
Propane (CAS 74-98-6)		
Acute		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
		658 mg/l/4h

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

**Skin corrosion/irritation** Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not available.

This product is not expected to cause skin sensitization. Skin sensitization

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Carcinogenicity

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

**Aspiration hazard** Not available.

12. Ecological information

The product is not classified as environmentally hazardous. However, this does not exclude the **Ecotoxicity** 

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

No data is available on the degradability of this product. Persistence and degradability

Bioaccumulative potential No data available. Partition coefficient n-octanol / water (log Kow)

Butane 2.89 Propane 2.36

Mobility in soil No data available.

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation Other adverse effects

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance

with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Do not re-use empty containers.

14. Transport information

DOT

UN1950 **UN** number

Aerosols, flammable **UN proper shipping name** 

Transport hazard class(es)

2.1 **Class** Subsidiary risk Label(s) None

Packing group Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions N82 Packaging exceptions 306 Packaging non bulk None Packaging bulk None

Product name: TERAND AUTO INTERIOR DETAILER & PROTECTOR

Product #: 1000009631 Version #: 01 Issue date: 06-03-2015

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

#### IATA

UN1950 **UN** number

Aerosols, flammable UN proper shipping name

Transport hazard class(es)

Class 2.1 Subsidiary risk 2.1 Label(s)

**Packing group** Not applicable.

**Environmental hazards** No. **ERG Code** 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed.

Cargo aircraft only **Packaging Exceptions** 

Allowed. LTD QTY

**IMDG** 

**UN** number UN1950 **UN** proper shipping name **AEROSOLS** Transport hazard class(es)

Class 2.1 Subsidiary risk

Label(s) None

**Packing group** Not applicable.

**Environmental hazards** 

Marine pollutant No.

**EmS** Not available.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

LTD QTY **Packaging Exceptions** 

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

This substance/mixture is not intended to be transported in bulk.

#### DOT







## 15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

## TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

#### **CERCLA Hazardous Substance List (40 CFR 302.4)**

Not listed

## SARA 304 Emergency release notification

Not regulated.

## OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

## Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No

Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

## SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

#### SARA 313 (TRI reporting)

Not regulated.

# Other federal regulations

## Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

## Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

Safe Drinking Water Act

Not regulated.

(SDWA)

## **US state regulations**

#### **US. Massachusetts RTK - Substance List**

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

## US. New Jersey Worker and Community Right-to-Know Act

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

## US. Pennsylvania Worker and Community Right-to-Know Law

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

## US. Rhode Island RTK

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

#### **US. California Proposition 65**

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

#### **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No

Country(s) or region Inventory name On inventory (yes/no)\* Europe European List of Notified Chemical Substances (ELINCS) Inventory of Existing and New Chemical Substances (ENCS) Japan No Korea Existing Chemicals List (ECL) No New Zealand New Zealand Inventory No **Philippines** Philippine Inventory of Chemicals and Chemical Substances No

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

Yes

SDS US

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

**Issue date** 06-03-2015

Version # 01

**Disclaimer** The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Product name: TERAND AUTO INTERIOR DETAILER & PROTECTOR