



6561 Palmer Park Circle Ste A
 Sarasota, FL 34238
 store.interstateproducts.com

Ph 800-474-7294

Fax 800-448-6329

SAFETY DATA SHEET

1.) PRODUCT INFORMATION

Date : February, 2020

HMISCODES

Trade Name: Traction N More (Part A)

Manufactured For Interstate Products, Inc.,

CAS Registry No. See below for individual ingredients

EMERGENCY TELEPHONE 800-424-9300

Telephone for Information 800-474-7294

Health	2
Flammability	3
Reactivity	0
Personal Protection	H

2.) HAZARDOUS INGREDIENTS

Section II A: Hazardous Ingredients

INGREDIENT	CAS#	(To Nearest 1.00%)			VAPOR PRESS
		% BYWT	%BY VOL	LEL	
Glycoether	2807-30-9	8.00	12.00	1.0	.20
High Flash Naphtha	64742-95-6	12.00	19.00	.5	2.70
Xylene	1330-20-7	5.60	8.60	1.0	21.00

Section II B: Occupational Exposure Limits

INGREDIENT	OSHA PEL'S			ACGIHTLV'S		
	OSHA ppm	OSHA mg/m3	TWA ppm	TWAmg/m3	STELppm	STELmg/m3
Glycoether	NA	NA	NA	NA	NA	NA
High Flash Naphtha	100	305.00	100	305.00	150	450.00
Xylene	100	NA	100	NA	150	NA

3.) PHYSICAL DATA

Boiling Point: 282-349 Degrees F
 Vapor Density: Heavier Than Air
 Solubility in Water: Nil

Appearance: Opaque Liquid
 Evaporation Rate: Slower Than Ether
 Pounds Per Gallon: 11.23
 2.87 lbs non-exempt solvent per adjusted gallon

Volatiles%	By Weight	By Volume
Total	25.6	39.1
ExemptVOC	0	0
Non-Exempt	25.6	39.1

4.) FIRE AND EXPLOSION HAZARD DATA

Flammability Classification:

OSHA: Flammable DOT: Flammable

Flash Point: 81.00 (Method Used): Tee

LEL: 7

Extinguishing Media: CO2 / Foam

Unusual Fire and Explosion Hazards: This material may be ignited by heat, sparks, flame, or static electricity. Keep containers closed when not in use. Isolate from heat, sparks, pilot lights, smoking materials, and other sources of ignition.

Special Firefighting Procedures: The use of SCBA is recommended for fire fighters. Water spray may be useful in cooling containers exposed to heat and flame. Avoid spreading burning liquid with water used for cooling purposes. Fight as volatile liquid fire. Closed containers may explode when exposed to extreme heat. Use water to cool fire exposed containers.

5.) REACTIVITY DATA

Stability: Stable

Conditions to Avoid: Heat, sparks, open flames, and static electricity.

Incompatibility (materials to avoid): Sources of ignition.

Hazardous Decomposition or Byproducts: CO2

Hazardous Polymerization: Will not occur.

6.) HEALTH HAZARD DATA

Routes of Entry:

Inhalation: Yes

Skin: Yes

Ingestion: Yes

Effects of Overexposure: Dizziness, nausea, vomiting, loss of coordination, and fatigue.

Medical Conditions Prone to Aggravation by Exposure: Asthma and heart conditions.

Emergency and First Aid Procedures: Skin: Flush with water, if redness persists, seek medical attention. Inhalation: **If** respiratory symptoms develop, remove victim from source of exposure to fresh air. **If** symptoms persist, seek medical attention. Ingestion: Seek emergency medical attention.

7.) SAFE HANDLING AND USE

Material Released or Spilled: Stay up wind. Remove source of ignition. Keep out of drains, sewers, and waterways. Use absorbent pads.

Waste Disposal Method: Dispose of in accordance with local, state, and federal regulations.

8.) CONTROL MEASURES

Respiratory Protection: Use approved organic supplied air respirator.

Ventilation: Mechanical, explosion proof.

Protective Gloves: Yes

Eye Protection: Yes

Other Protective Clothing or Equipment: Wear impervious clothing.

Work Hygienic Practices: Wash thoroughly before eating.

9.) SPECIAL PRECAUTIONS

Keep in cool, properly ventilated, explosion proof area.

Keep away from heat, sparks, and open flames.

Use approved grounding equipment to avoid static sparks.

Note: This product contains Xylol and is subject to the reporting requirements of SARA 313 and 40 CFR 372.

NOTICE: The information contained on this Material Safety Data Sheet is considered accurate as of the date of publication. It is not necessarily all inclusive or fully adequate in every circumstance. The suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements. No warranty, express or implied, of merchantability, fitness, accuracy of data, or the results to be obtained from the use thereof is made. The supplier assumes no responsibility for injury or damages resulting from the inappropriate use of this product.



6561 Palmer Park Circle Ste A
Sarasota, FL 34238
store.interstateproducts.com

Ph 800-474-7294

Fax 800-448-6329

SAFETY DATA SHEET

1.) PRODUCT INFORMATION

Date: February 2020

HMISCODES

Trade Name Traction N More (Part B)

Manufactured For Interstate Products, Inc.,

CAS Registry No. See below for individual ingredients

EMERGENCY TELEPHONE 800-424-9300

Telephone for Information 800-474-7294

Health 2

Flammability 3

Reactivity 0

Personal Protection H

2.) HAZARDOUS INGREDIENTS

Section II A: Hazardous Ingredients

INGREDIENT	CAS#	(To Nearest 1.00%)		LEL	VAPOR PRESS
		% BYWT	% BY VOL		
Glycoether	2807-30-9	7.00	8.00	1.0	.20
High Flash Naphtha	64742-95-6	3.00	4.00	.5	2.70
Xylene	1330-20-7	14.57	18.22		

Section II B: Occupational Exposure Limits

INGREDIENT	OSHA PEL'S			ACGIH TLV'S		
	OSHA ppm	OSHA mg/m3	TWA ppm	TWA mg/m3	STEL ppm	STEL mg/m3
Glycoether	NA	NA	NA	NA	NA	NA
High Flash Naphtha	100	305.00	100	305.00	150	450.00
Xylene						

3.) PHYSICAL DATA

Boiling Point: 282-349 Degrees F

Vapor Density: Heavier Than Air

Solubility in Water: Nil

Appearance: Clear Liquid

Evaporation Rate: Slower Than Ether

Pounds Per Gallon: 9.07

2.28 lbs non-exempt solvent per adjusted gallon

Volatiles%	By Weight		By Volume	
Total	25.1		31	
ExemptVOC	0		0	
Non-Exempt	25.1		31	

4.) FIRE AND EXPLOSION HAZARD DATA

Flammability Classification:

OSHA: Flammable

DOT: Flammable

Flash Point: 81.00 (Method Used): Tee

LEL: 7

Extinguishing Media: CO2 / Foam

Unusual Fire and Explosion Hazards: This material may be ignited by heat, sparks, flame, or static electricity. Keep containers closed when not in use. Isolate from heat, sparks, pilot lights, smoking materials, and other sources of ignition.

Special Firefighting Procedures: The use of SCBA is recommended for fire fighters. Water spray may be useful in cooling containers exposed to heat and flame. Avoid spreading burning liquid with water used for cooling purposes. Fight as volatile liquid fire. Closed containers may explode when exposed to extreme heat. Use water to cool fire exposed containers.

5.) REACTIVITY DATA

Stability: Stable

Conditions to Avoid: Heat, sparks, open flames, and static electricity.

Incompatibility (materials to avoid): Sources of ignition.

Hazardous Decomposition or Byproducts: CO2

Hazardous Polymerization: Will not occur.

6.) HEALTH HAZARD DATA

Routes of Entry:

Inhalation: Yes

Skin: Yes

Ingestion: Yes

Effects of Overexposure: Dizziness, nausea, vomiting, loss of coordination, and fatigue.

Medical Conditions Prone to Aggravation by Exposure: Asthma and heart conditions.

Emergency and First Aid Procedures: Skin: Flush with water, if redness persists, seek medical attention.

Inhalation: **If** respiratory symptoms develop, remove victim from source of exposure to fresh air. **If** symptoms persist, seek medical attention. Ingestion: Seek emergency medical attention.

7.) SAFE HANDLING AND USE

Material Released or Spilled: Stay up wind. Remove source of ignition. Keep out of drains, sewers, and waterways. Use absorbent pads.

Waste Disposal Method: Dispose of in accordance with local, state, and federal regulations.

-I CONTROL MEASURES

Respiratory Protection: Use approved organic supplied air respirator.

9.) SPECIAL PRECAUTIONS

Keep in cool, properly ventilated, explosion proof area.

Keep away from heat, sparks, and open flames.

Use approved grounding equipment to avoid static sparks.

Note: This product contains Xylol and is subject to the reporting requirements of SARA 313 and 40 CFR 372.

NOTICE: The information contained on this Material Safety Data Sheet is considered accurate as of the date of publication. It is not necessarily all inclusive or fully adequate in every circumstance. The suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements. No warranty, express or implied, of merchantability, fitness, accuracy of data, or the results to be obtained from the use thereof is made. The supplier assumes no responsibility for injury or damages resulting from the inappropriate use of this product.



6561 Palmer Park Circle Ste A
 Sarasota, FL 34238
 store.interstateproducts.com

Ph 800-474-7294

Fax 800-448-6329

SAFETY DATA SHEET

1.) PRODUCT INFORMATION

Date February 2020
Trade Name Traction N More (Sand)
Manufactured For Interstate Products, Inc.,
CAS Registry No. See below for individual ingredients
EMERGENCY TELEPHONE 800-282-7769
Telephone for Information 800-474-7294

2.) HAZARDOUS INGREDIENTS

HAZARDOUS COMPONENTS	CAS REGNO	OPTWT%	PEUTI..V
Silicon Dioxide SiO2	14808-60-7	10mg/m ³ 8 hrTWA	0.1 mg/m ³ 310hrTWA

3.) PHYSICAL DATA

Boiling Point: 4046 Degrees F	Specific Gravity (Water= 1): 2.65
Vapor Pressure (mm Hg): None	Melting Point: 3050 Degrees C
Vapor Density (water=1): None	Evaporation Rate: None
Appearance and Odor: White or tan sand, granular, odorless	(Butyl Acetate=1)
Solubility in Water: Insoluble	

4.) FIRE AND EXPLOSION HAZARD DATA

Flash Point (method used): None
 Flammable Limits: None
 Extinguishing Media: None required. Sand may be used as an extinguishing media.
 Special Fire Fighting Procedures: NA
 Unusual Fire and Explosion Hazards: NA

5.) REACTIVITY DATA

Stability: Stable
 Conditions to Avoid: None
 Incompatibility (materials to avoid): Contact with powerful oxidizing agents, such as Fluorine may cause fires.
 Hazardous Decomposition or Byproducts: Silica will dissolve Hydrofluoric Acid and produce a corrosive gas (Silicon Tetrafluoride).
 Hazardous Polymerization: Will not occur.
 Conditions to Avoid: None

6.) HEALTH HAZARD DATA

Routes of Entry:

Inhalation: Yes Skin: No Ingestion: No

Health Hazards (Acute & Chronic): Inhalation: Prolonged exposure to respirable Crystalline Quartz may cause delayed, chronic lung injury, Silicosis. Skin: Not likely to cause irritation. Ingestion: Not likely to cause irritation. Eyes: May cause slight, temporary irritation.

Carcinogenicity:

NTP: No IARC Monographs: Yes OSHA Regulated: No

IARC concludes that there is sufficient evidence for the carcinogenicity of Crystalline Silica to experimental animals, and that there is limited evidence of the carcinogenicity to humans.

Medical Conditions Generally Aggravated by Exposure: Respiratory and pulmonary disorders. Smoking aggravates the effects of exposure.

Emergency and First Aid Procedures: Eyes: Flush with water, see physician if necessary. Inhalation: For gross inhalation, remove to fresh air, give artificial respiration, as needed and seek medical attention.

7.) SAFE HANDLING AND USE

Material Released or Spilled: Vacuum and place into closable container for disposal, or flush with water. DO NOT dry sweep.

Waste Disposal Method: According to federal, state, and local authorities.

Precautions for Storing and Handling: Avoid breakage and dusting.

8.) CONTROL MEASURES

Respiratory Protection: When particulate concentration is up to five times PEL, use any NIOSH or MSHA approved respirator.

Ventilation: Local exhaust

Protective Gloves: Optional

Eye Protection: Safety glasses

Other Protective Clothing or Equipment: Optional

Work Hygienic Practices: Avoid creating and breathing dust

NOTICE: The information contained on this Material Safety Data Sheet is considered accurate as of the date of publication. It is not necessarily all inclusive or fully adequate in every circumstance. The suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements. No warranty, express or implied, of merchantability, fitness, accuracy of data, or the results to be obtained from the use thereof is made. The supplier assumes no responsibility for injury or damages resulting from the inappropriate use of this product.