

## Chemical Compatibility Guide for Ultra-Containment Berms

According to EPA guidelines, spills must be cleaned up with 24 hours and any secondary containment areas must be inspected once a week. The chart below lists chemical compatibility of Copolymer 2000. The information has been developed from industry available data and offers compatibility based on exposure of one week or less.

The rating system is indicated as

**A-** Fluid has little or no effect at room temperature

**B-** Fluid has minor to moderate effect at room temperature

**C-** Fluid has severe effect at room temperature

Chemical	Copolymer 2000
Kerosene	A
Diesel Fuel	A
Ohio Crude Oil	A
Hydraulic Fluid- Petroleum Based	A
Naptha	A
Conc. Ammonia Hydroxide	A
50% Acetic Acid	C
50% Phosphoric Acid	A
50% Hydrochloric Acid	A
50% Nitric	C
50% Sulfuric Acid	A
60% Sodium Hydroxide	A
Methyl Alcohol	A
JP-4 Jet Fuel	A
Salt Water 180°F	A
Phthalate Plasticizers	B
SAE-30 Oil	A
Raw Linseed Oil	A

**\*IMPORTANT USER NOTICE FOR CHEMICAL COMPATIBILITY GUIDES**

The data contained herein is a compilation of existing published data from leading manufacturers and does not represent actual testing performed by UltraTech International, Inc.

This listing is offered only as a guide and utilizes information which, to the best of UltraTech's knowledge, is accurate and reliable. Due to variables and conditions of application beyond the control of UltraTech, none of the data shown in this guide is to be construed as a guarantee, expressed or implied. UltraTech International, Inc. assumes no responsibility, obligation or liability in conjunction with the use or misuse of the information herein.