



INTERSTATE PRODUCTS, INC.

“Your Road to Quality Environmental Products Since 1996”

Click to Call NOW  1-800-474-7294

Power-Patch Concrete Epoxy Kit (Grey) Spec Sheet

Power-Patch Kit covers 50 sq. ft at 1/8" thickness but may be applied thicker.

Power Patch 970 Specifications:

Volatile Organic Content: Zero

Compressive Strength: 8400

PSI at ASTMD: 695

Impact Resistance: Excellent

Abrasion Resistance: Excellent

Tensile Strength: 6700 PSI @ ASTMD638

Flexural Strength: 11000 PSI @ ASTMD790

Primer: None Required

Topcoat: None Required

Pot Life: 20 Minutes @ 70°F - keep mixing hotter

temperatures could cause less pot life

Shelf Life: 2 years in unopened containers



SKU: Patch : **AC-970**

SHIPPING: Calculated at Checkout

SDS: Part A, B, & C

CONCRETE PATCH LABEL: Label

TYPE: Epoxy Patch

NOT FOR SALE IN CALIFORNIA:

California Customers May Purchase AC-680



A concrete crack patch repair kit packed in a 5 gallon mixing bucket and includes epoxy resin, hardener, and aggregate for the strongest possible repairs for patch and resurfacing on concrete. This 100% epoxy concrete patch & repair kit is used on plant floors, garage floor, sidewalks, driveways, basement floor. bricks, stones, steps and walls applications. Excellent also for use on floor areas which are subjected to heavy abrasive traffic, high impact and corrosive spillage. Bonds to concrete, metal, wood, & more. Just mix up and trowel down onto concrete surface for long lasting filler and bonding action. * Most popular repair kit. When resurfacing only is required, mix parts A and B only and roll down or skim coat with a trowel. Power-Patch may be feathered down to 1/16 of an inch. Use for permanent repair jobs with easy instruction on product label. No extra bonder is needed. 24 to 48 hour dry time in warm weather. For use inside and outdoor repair.

*Temperature must be 50° F or higher for 48 hours. Check with us on low temperature options.