



# INTERSTATE PRODUCTS, INC.

"YOUR ROAD TO QUALITY ENVIRONMENTAL PRODUCTS SINCE 1996"

## NON-SLIP COATING TRACTION-N-MORE INSTRUCTIONS

1. REVIEW MATERIAL SAFETY DATA SHEET FOR SAFETY PRECAUTIONS.
2. REVIEW LABEL FOR SAME AND ANY UPDATES.
3. CLEAN FLOOR, SLIGHT ACID RINSE IF NEEDED.
4. ANY POLISHED SMOOTH SURFACES A PRIMER OR ROUGHING UP MAY BE NEEDED.
5. MIX CANS A AND B
  - LET STAND FOR 30 MINUTES TO ACTIVATE.
6. ROLL IT DOWN WITH A PHENOLIC CORE ROLLER.
7. HEAVY DUTY AREAS APPLY SECOND COAT 24 HOURS AFTER FIRST.
8. BROADCAST AGGREGATE EVENLY OVER THE LAST COAT YOU APPLY.
  - THINK OF IT AS BREADING A CHICKEN CUTLET WITH A NICE UNIFORM COAT.
9. DRY TIME MAY VARY BUT EXPECT:
  - 24 HOURS TO WALK ON.
  - 48 HOURS TO DRIVE ON.
  - BASED ON 50° F AND ABOVE.

**IF YOU HAVE ANY QUESTIONS DURING YOUR APPLICATION PROCESS,  
PLEASE CALL US AT 1-800-474-7294.**



INTERSTATE PRODUCTS, INC.  
5585 MARQUESAS CIRCLE UNIT 10-C  
SARASOTA, FL 34233  
[HTTPS://STORE.INTERSTATEPRODUCTS.COM](https://store.interstateproducts.com)  
USA: 1-800-474-7294 (TOLL FREE)  
INTERNATIONAL: 1-941-377-8610



SERVING THE INDUSTRY 1996