

Interstate Products, Inc.

5585 Marquesas Circle Unit 10-C Sarasota, FL 34233 1-800-474-7294 • Fax
1-800-448-6329 **Outside the U.S.:** Phone 941-377-8610 • Fax 1-941-379-092

Please visit us on the web...

<http://store.interstateproducts.com>



NON-SLIP — Frequently Asked Questions

Question: How long does it take to dry?

Answer: Dry time: 12 hours = tacky 24 hours = walk on 48 hours = drive on

Question: Will this seal my surface or provide skid resistance?

Answer: IPI Non Slip coating will seal and provide skid resistance to help protect and prolong the life of your surface.

Question: What is the minimum temperature i can apply non-slip coating in?

Answer: It must be 50°F or higher for 48 hours after applying the product. If you need a product that works in colder temperatures, please contact us directly.

Question: Do I need to apply 2 coats?

Answer: You can if you wish, in most cases it's not necessary if you have applied it correctly. If you elect to apply an additional coat make sure to allow the first coat to dry and then reapply a second coat. The second coat doesn't need to be as heavy as the first coat.

Question: Can a sealer on my surface effect the products bonding?

Answer: Yes. You should remove or scratch the surface up before applying. These products work best for long lasting results when they can penetrate and bond to the concrete.

Question: What colors are available?

Answer: We have 18 standard colors or you may send a custom color chip that we can match for you.

Question: Why would I get more or less coverage?

Answer: The coverage amount is different depending on how porous the surface is. For example, wood or brand new concrete may soak up more than cured concrete. Normally the coverage listed is accurate.

Question: Can I get it in a custom color?

Answer: Yes, we would need a sample color or a color code that we can work with. However we don't say we can match an existing color because of wear and tear and fading that may have occurred since the color was applied. We will get it as close as we can and the color match is not guaranteed or returnable.

Question: Are there discounts for Bulk purchases?

Answer: Yes! Depending on the amount of kits purchased we will always work with our client's needs.

Question: Can I store this product if I don't use all of it once I have mixed it?

Answer: No, once you mix the product you must use all of that kit. Use the entire kit that has been mixed and don't mix more than you can apply.

Differences between Traction-N-More Non-Slip Coating, and Safety Seal Anti Slip Coating: Traction-N-More is a traditional heavy duty A and B resin and hardener epoxy mix with an aggregate. Mix the A and B and then paint over the area. Then broadcast the aggregate evenly in a uniform manner. Traction-N-More leaves an industrial non-slip sandpaper finish that can stand up to many chemicals and most forklift traffic. You may also purchase our "BARE FEET" product. It's a blend of the same industrial product, but with a less coarse aggregate made for bare feet and livestock.

Safety Seal Anti Slip Coating is a resin polymer for indoor concrete only. It comes in a 5 gallon bucket and you just need to mix it before use. It is meant for less industrial type applications and indoor only.

New products include cold temperature non-slip coating as well as the "Barefeet" version of the Traction and More, which has a lower profile grit. Since 1996 Interstate products and has been providing solutions for all types of safety and facility management. Contact us today for more information and Learn the IPI difference, where we provide unsurpassed service on every product we sell.